

How to implement WN.C WebChat

- 1) Acquire ClientId by making an enquiry at <http://worldnet.club/wncwebchat/>
- 2) Connect the wnc-widget.js script to your page before it's place of use
- 3) Issue a call to the creating widget feature

```
widgetId = WNC.Widgets.Dialog(options, funcs);
```

The feature WNC.Widgets.Dialog returns the widget ID necessary for additional interaction with the widget.

Object options

Parameter name	Description	Type	Expected value
target*	Expected behavior of the widget	string	"window" – widget will be opened in a new window, "frame" – widget will be opened as a part of the parent window
clientId*	Client ID (see point 1)	string	
objId	The element ID to which the widget will be connected to (Only for the target: "frame")	string	
height	The widget height (Only for the target: "frame")	number	
theme	The widget theme	string	"widget-blue" – blue theme (set by default) "widget-red" – red theme

EXAMPLE

```
var options = {
  target: "window",
  clientId: 0,
}
```

EXAMPLE

```
var options = {
  target: "frame",
  clientId: 0,
  height: 400,
  objId: "CalendarPlanDialog",
}
```

Object funcs (optional parameter)

Parameter name	Description	Type	Expected value
onInit	Initiated at the widget initialization	function	Object PageId – user ID on WN.C
onLogin	Initiated at the entering the system using the widget	function	Token – authentication token RefreshToken – token of

			authentication refresh
onOpenDialog	Initiated at the opening of a dialogue	function	Object DialogId – dialogue ID on WN.C
onCreateDialog	Initiated at creating a dialogue	function	
onUnloadWidget	Initiated at closing a dialogue	function	

EXAMPLE

```

var funcs = {
  onInit: function (data) {
    SaveWncPageInfo(data.PageId, data.Token, data.RefreshToken);
  },
  onLogin: function (data) {
  },
  onOpenDialog: function (data) {
  },
  onCreateDialog: function (data) {
    SaveWncDialogId(wncCalendarPlanId, data.DialogId);
  },
  onUnloadWidget: function (data) {
    WNC.API.OnUnloadWidget(widgetId);
    widgetId = null;
  }
}

```

Description of WNC.API features

Feature	Parameters		Description
WNC.API.OpenDialog	widgetId	String Widget ID	Opens existing dialogue or creates a new one
	dialogId	String Dialogue ID on WN.C (null, to create a new dialogue)	
	dialogName	String Dialogue name	
	dialogParticipants	Array of string List of dialogue participants	
	token	String Chat administrator's token	
WNC.API.UnloadWidget	widgetId	String Widget ID	Initiated for uploading the widget to the client